



Polyurethane equipment wheel

Quieter and smoother roll

Manner has further improved the ESI wheel range. The improvements made will change the appearance, colour and tread hardness of the equipment castors. Tread hardness has been reduced by utilizing soft polyurethane material. As a result, the castor rolls quieter and smoother, and grips the surface better.

Further advantages of the improvements are:

- rounder tread profile = lower rolling resistance
- more modern appearance
 - new tread profile
 - large plastic thread guard design for wheels with ball bearings
- improved hydrolysis resistance (better suitability for humid conditions)
- darker tread provides cleaner look even when dirty

The new ESI-NP wheel will have a new light gray center colour. Metal thread guards will be made available for wheels with plain bearings also in future.

Technical information

Wheel diameter	75, 100 and 125 mm
Fork material	Metal (ES-series)
Rated load	90 - 105 kg
Fitting options	Bolt hole, threaded stem, rectangular top plate, tube expander
Bearing of the wheel	Ball or plain bearing
Wheel material	Soft polyurethane
Tread hardness	80 Shore A
Thread guard	Plastic in wheels with ball bearings Metal in wheels with plain bearings



Oy Mannerin Konepaja Ab, P.O.Box 3, 10901 Hanko, Finland
Tel. +358-19-222 001, Fax +358-19-248 2000
E-mail: manner@manner.fi, Internet: www.manner.fi

