



Two-stage brake for Tango castors

The two-stage brake for Tango separates the function of total-stop brake into directional-lock and total-stop brake. The brake pedal has two positions. Pressing the brake pedal halfway down locks the swivel in the running direction, and pressing the pedal all the way down locks also the wheel, providing total-stop.

Two-stage brake is ideal for devices that need to separate directional lock and total-stop brake into two separate functions, depending on the situation.

The two-stage brake feature is available for 125 mm Tango castors.

Technical information

| | |
|------------------------|---|
| Wheel diameter | 125 mm |
| Fork material | Glass-fibre reinforced polyamide |
| Rated load | 70–110 kg |
| Fitting options | M10x16 threaded stem M12x16 threaded stem Plastic rectangular top plate Expanders for round or square tube |
| Wheel material | Polypropylene center and thermoelastic rubber tyre Polyamide center and elastic solid-rubber tyre |
| Bearing of the wheel | Ball bearing or plain bearing |
| Tread hardness | Thermoelastic rubber: 55, 80 and 90 shore A Elastic solid-rubber tyre: 60 Shore A |
| Height | 125 mm threaded stem – 161 mm 125 mm rectangular top plate – 168 mm Expander – 161 mm |
| Standard colour | |
| Fork and thread guards | Grey RAL 7042 Light grey RAL 7035 Black |



Oy Mannerin Konepaja Ab, P.O.Box 3, 10901 Hanko, Finland
Tel. +358 19 222 001, Fax +358 19 248 2000
E-mail: manner@manner.fi, Internet: www.manner.fi

