



## GKR-S-125 PTE/K 80 NM

304933

**Product type:** Swivel castors  
**Product group:** Tango  
Non-magnetic

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gkr-s-125-pte-k-80-nm](http://www.manner.fi/en/tuote/gkr-s-125-pte-k-80-nm)

### Technical data

	Wheel diameter (mm):	125	<b>Sh A</b>	Hardness of the tread (shore A):	80
	Wheel width (mm):	32		Centre material:	Polypropylene
	Load capacity (kg):	70		Bearing type:	Ball bearing
	Overall height (mm):	161		Fitting:	Threaded stem
	Swivel radius (mm):	110		Weight (kg):	0.46
	Fork material:	Plastic		Threaded stem diameter x len...	10x16
	Color:	Grey		Bore length (mm):	
	Special features:	Non-magnetic		Tread material:	Thermoplastic rubber