



## GKL-R-S-100 NEK/K 301807

**Product type:** Others

**Product group:** Tango

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gkl-r-s-100-nek-k](http://www.manner.fi/en/tuote/gkl-r-s-100-nek-k)

### Technical data

|  |                               |            |  |                                       |                       |
|--|-------------------------------|------------|--|---------------------------------------|-----------------------|
|  | Wheel diameter (mm):          | 100        |  | Sh A Hardness of the tread (shore A): | 60                    |
|  | Wheel width (mm):             | 32         |  | Centre material:                      | Polyamide             |
|  | Load capacity (kg):           | 80         |  | Bearing type:                         | Ball bearing          |
|  | Overall height (mm):          | 148        |  | Fitting:                              | Rectangular top plate |
|  | Swivel radius (mm):           | 95         |  | Weight (kg):                          | 0.566                 |
|  | Plate length x width (mm):    | 77X67      |  | Hole centres length x width (mm):     | 61/51X50/42           |
|  | Fastening hole diameter (mm): | 8          |  | Brake type:                           | Directional brake     |
|  | Brake control:                | Individual |  | Tread material:                       | Elastic solid rubber  |

Smart Moves on Manner Castors.