



## GKL-R-S-100 PTE/K 80 301811









**Product type:** Swivel castors with directional lock  
**Product group:** Tango

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.










[www.manner.fi/en/tuote/gkl-r-s-100-pte-k-80](http://www.manner.fi/en/tuote/gkl-r-s-100-pte-k-80)

### Technical data

	Wheel diameter (mm):	100
	Wheel width (mm):	32
	Load capacity (kg):	100
	Overall height (mm):	148
	Swivel radius (mm):	95
	Plate length x width (mm):	77X67
	Fastening hole diameter (mm):	8
	Brake control:	Individual

**Sh A** Hardness of the tread (shore A):80

	Centre material:	Polypropylene
	Bearing type:	Ball bearing
	Fitting:	Rectangular top plate
	Weight (kg):	0.52
	Hole centres length x width (...)	61/51X50/42
	Brake type:	Directional brake
	Tread material:	Thermoplastic rubber