



## GKL-R-S-125 NEK/K 301711

**Product type:** Swivel castors with directional lock

**Product group:** Tango

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gkl-r-s-125-nek-k](http://www.manner.fi/en/tuote/gkl-r-s-125-nek-k)

### Technical data

	Wheel diameter (mm):	125		Hardness of the tread (shore A):	60
	Wheel width (mm):	32		Centre material:	Polyamide
	Load capacity (kg):	100		Bearing type:	Ball bearing
	Overall height (mm):	168		Fitting:	Rectangular top plate
	Swivel radius (mm):	110		Weight (kg):	0.683
	Plate length x width (mm):	77X67		Hole centres length x width (mm):	61/51X50/42
	Fastening hole diameter (mm):	8		Brake type:	Directional brake
	Brake control:	Individual		Tread material:	Elastic solid rubber