



## GK-JG-S-125 PTE/K 80 IX-12 304085

**Product type:** Swivel castors with brake



















**Product group:** Tango  
Stainless

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gk-jg-s-125-pte-k-80-ix-12](http://www.manner.fi/en/tuote/gk-jg-s-125-pte-k-80-ix-12)

### Technical data

	Wheel diameter (mm):	125		Sh A Hardness of the tread (shore A):	80
	Wheel width (mm):	32		Centre material:	Polypropylene
	Load capacity (kg):	100		Bearing type:	Ball bearing
	Overall height (mm):	161		Fitting:	Bolt hole
	Swivel radius (mm):	107		Bolt hole diameter (mm):	12
	Weight (kg):	0.477		Fork material:	Plastic
	Brake type:	Total-stop brake		Brake control:	Individual
	Color:	Grey		Bore length (mm):	
	Special features:	Stainless		Tread material:	Thermoplastic rubber