

# GK-JY-S-100 PTE/K A
# 301835

**Product type:** Swivel castors with brake
**Product group:** Tango
Conductive

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.

www.manner.fi/en/tuote/gk-jy-s-100-pte-k-a

## Technical data

| | | | |
|---|---|---|---|
| Wheel diameter (mm): | 100 | Hardness of the tread (shore A): | 86 |
| Wheel width (mm): | 32 | Centre material: | Conductive polypropylene |
| Load capacity (kg): | 80 | Bearing type: | Ball bearing |
| Overall height (mm): | 141 | Fitting: | Bolt hole |
| Swivel radius (mm): | 95 | Bolt hole diameter (mm): | 10 |
| Weight (kg): | 0.394 | Fork material: | Conductive glass fiber reinforced polyamide |
| Brake type: | Total-stop brake | Brake control: | Individual |
| Color: | Dark grey | Bore length (mm): | |
| Special features: | Conductive | Tread material: | Conductive thermopl. rubber |