



GKL-JY-S-125 PTE/K A 301853











Product type:	Swivel castors with brake
Product group:	Tango
	Conductive

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.












www.manner.fi/en/tuote/gkl-jy-s-125-pte-k-a

Technical data

	Wheel diameter (mm):	125
	Wheel width (mm):	32
	Load capacity (kg):	80
	Overall height (mm):	168
	Swivel radius (mm):	110
	Fork material:	Conductive glass fiber reinforced polyamide
	Fastening hole diameter (mm):	8
	Brake control:	Individual
	Bore length (mm):	
	Tread material:	Conductive thermopl. rubber

Sh A Hardness of the tread (shore A):86

	Centre material:	Conductive polypropylene
	Bearing type:	Ball bearing
	Fitting:	Rectangular top plate
	Weight (kg):	0.605
	Plate length x width (mm):	77x67
	Hole centres length x width (...)	61/51X50/42
	Brake type:	Total-stop brake
	Color:	Dark grey
	Special features:	Conductive