



GKL-S-100 PTE/K A

301845


















Product type:	Swivel castors
Product group:	Tango
	Conductive

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



www.manner.fi/en/tuote/gkl-s-100-pte-k-a

Technical data

	Wheel diameter (mm):	100	Sh A	Hardness of the tread (shore A):	86
	Wheel width (mm):	32		Centre material:	Conductive polypropylene
	Load capacity (kg):	80		Bearing type:	Ball bearing
	Overall height (mm):	148		Fitting:	Rectangular top plate
	Swivel radius (mm):	95		Weight (kg):	0.434
	Fork material:	Conductive glass fiber reinforced polyamide		Plate length x width (mm):	77x67
	Fastening hole diameter (mm):	8		Hole centres length x width (...)	61/51X50/42
	Bore length (mm):			Color:	Dark grey
	Tread material:	Conductive thermopl. rubber		Special features:	Conductive