



## GKL-S-100 PTE/K A 301845

**Product type:** Swivel castors

**Product group:** Tango  
Conductive

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gkl-s-100-pte-k-a](http://www.manner.fi/en/tuote/gkl-s-100-pte-k-a)

### Technical data

	Wheel diameter (mm):	100		Sh A Hardness of the tread (shore A):	86
	Wheel width (mm):	32		Centre material:	Conductive polypropylene
	Load capacity (kg):	80		Bearing type:	Ball bearing
	Overall height (mm):	148		Fitting:	Rectangular top plate
	Swivel radius (mm):	95		Weight (kg):	0.434
	Fork material:	Conductive glass fiber reinforced polyamide		Plate length x width (mm):	77x67
	Hole centres length x width (mm):	61/51X50/42		Fastening hole diameter (mm):	8
	Color:	Dark grey		Bore length (mm):	
	Special features:	Conductive		Tread material:	Conductive thermopl. rubber