



## GKL-S-125 PTE/K 80

### 301688

















**Product type:** Swivel castors  
**Product group:** Tango

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gkl-s-125-pte-k-80](http://www.manner.fi/en/tuote/gkl-s-125-pte-k-80)

### Technical data

	Wheel diameter (mm):	125	<b>Sh A</b> Hardness of the tread (shore A):80	
	Wheel width (mm):	32	 Centre material:	Polypropylene
	Load capacity (kg):	100	 Bearing type:	Ball bearing
	Overall height (mm):	168	 Fitting:	Rectangular top plate
	Swivel radius (mm):	110	 Weight (kg):	0.566
	Fork material:	Plastic	 Plate length x width (mm):	77X67
	Hole centres length x width (...)	61/51X50/42	 Fastening hole diameter (mm):	8
	Color:	Grey	 Bore length (mm):	
	Tread material:	Thermoplastic rubber		